



TECHNICAL BULLETIN

PROFESSIONAL PRO SPEED COMPOUND

Part #:	M10032 - 32 oz M10001 – 1 gallon
Packaging:	32 oz Compound- 6 per case 1 Gallon Compound- 4 per case
Features:	<ul style="list-style-type: none">• Fast cutting compound with advanced technology• Quick removal of 1200 grit and finer sanding marks for easier polishing• Removes deep scratches, acid rain or severe swirls/holograms• Works great on fresh and cured paints
pH:	8.4 – 8.9
Paintable:	Yes
Dilution:	RTU (Ready to use)
Application Method:	Rotary
Directions:	SHAKE WELL. For best results, apply to a clean, cool properly cured paint surface. Set rotary buffer to approximately 1200 – 1800 RPM's and work one section at a time using your favorite Meguiar's Wool Cutting Pad. Apply Pro Speed Compound (M100) directly to the paint surface and begin working in a 2' x 2' area with overlapping passes. Buff area using light to medium pressure. Reduce pressure when compound begins to dry. Continue working until defects or sanding marks are removed. Wipe off remaining residue with a Meguiar's Ultimate Wipe (M9910) prior to polishing. For final polishing, please choose the appropriate Meguiar's Foam Pad and your favorite Meguiar's polish.
Health rating:	Health: 2 Fire: 1 Reactivity: 0 Specific Hazard: None

FOR ADDITIONAL SAFETY INFORMATION, CONSULT MSDS
KEEP OUT OF REACH OF CHILDREN